



# 750-900CFM

DUAL PRESSURE \ TIER 4 FINAL - STAGE V \ CUMMINS ENGINE \ PORTABLE COMPRESSOR



750CFM / 100/150PSI   825CFM / 100/150PSI   900CFM / 100/150PSI



# SPECIFICATIONS

## Compressor

Type	Single Stage, oil flooded rotary screw
Ambient Oper. Temp. Range	-40° to + 125°F [-40° to +52°C]
Oil Capacity	42 gal. (114 L)
Air Service Connections	2" NPT
Operating Pressure Range	90-150 psig (6.2 - 10.3 Bar)
Estimated Weight, Serviced	9,000 lbs
Dimensions L x W x H (in")	215.2" x 76.6" x 88.1"

## Engine

Type	Diesel
Make & Model	CUMMINS QSB6.7 Tier 4 Final - Stage V
Idle Speed	1400 RPM
Fuel Tank Capacity	150 gal (568 L)
Horsepower @ rated RPM	310 hp (231 kW)
Full Load Speed	1900 RPM
DEF Volume	15 gal (56.8 L)

## Models

Model	Rated Delivery	Rated Operating Pressure
D750PH4CU5	750 cfm (21.2 m <sup>3</sup> /min)	100/150 psig (6.9/10.4 Bar)
D825PH4CU5	825 cfm (23.3 m <sup>3</sup> /min)	100/150 psig (6.9/10.4 Bar)
D900PH4CU5	900 cfm (26.4 m <sup>3</sup> /min)	100/150 psig (6.9/10.4 Bar)

Sullivan-Palatek Electronic Controller (SPEC)



## FEATURES

- » Large 204mm Diameter Twin Screw Air End Manufactured In The USA by Sullivan-Palatek
- » Three Year Unlimited Hour Air End Warranty
- » Automatic 0 to 100% Capacity Control
- » 2" Service Connection
- » Oil Level Sight Gauge
- » Cummins Engine
- » Aluminized Fuel Tanks
- » Single Point Lifting Bail
- » Dual-Axle Running Gear
- » Adjustable 3" Lunette Eye
- » Noise Level Limited to Maximum of 76 dBA at 7 Meters
- » Automatic Shutdown and Protection System
- » Electric Brakes Standard
- » Galvanneal sheet metal
- » Block Heater standard with Cummins Engine
- » E-Z Lube Axle Bearings
- » Containment Base
- » Automatic Blowdown Valve
- » Large Service Doors for ease of Maintenance

## CONTROLLER

### Sullivan-Palatek Electronic Controller (SPEC)

Digital Readouts:

- » Compressor temperature
- » Discharge Pressure
- » Engine oil pressure
- » Engine Coolant temperature
- » Voltmeter
- » Tachometer
- » Fuel level - low fuel warning and shutdown
- » Complete engine diagnostic tool
- » Unit converter
- » Multilingual capabilities
- » Waterproof IP66/67
- » Air Filter Service
- » After cooler filter warning

**Sullivan-Palatek, Inc.**

1201 West US Highway 20  
Michigan City, IN 46360

219.874.2497    sullivan-palatek.com    info@palatek.com

Distributed by:-  
**Aggressive Air Compressor Co.**  
24580 Five Mile Rd.  
Redford MI 48239  
Tel. 313-541-2825  
[www.aggressive-air.com](http://www.aggressive-air.com)